



OVERVIEW

- ♦ The LA603 series is a premium grade specifically designed for long-term, dependable service with the benefits of indirect lighting
- ♦ A low-profile suspended direct/indirect fixture housing for attractive glare-free ambient lighting. Micro-perforated baffle with white opal acrylic inlay combines soft down-light with even ceiling illumination. Hinged baffle.

CONSTRUCTION

- ♦ Housing—Manufactured from code gauge steel for premium strength and rigidity
- ♦ Features durable steel bodies, quality paint finishes and superior electrical components
- ♦ Diffuser—Direct/indirect wide beam perforated diffuser for uniform ceiling illumination for a glowing, low brightness luminance
- ♦ Finish—Prior to painting, all metal parts are treated with a multi-stage phosphate bonding process to ensure adhesion and inhibit rusting. Powder coated with lighting grade white, having a reflectance factor exceeding 87% for premium quality and durability

PROJECT _____

TYPE _____

QTY. _____

APPLICATIONS

- ♦ Schools
- ♦ Offices
- ♦ Spaces utilizing video display terminals
- ♦ Locations requiring a visually comfortable environment

INSTALLATION

- ♦ Able to be cable, or stem mounted individually or in continuous rows
- ♦ Suspension mount options to suit your application; standard stem & canopies or aircraft cable

ELECTRICAL

- ♦ All electrical components are UL or ETL Listed. Lamp holders provided ensure positive lamp retention.
- ♦ Sufficient knock-outs are provided for connections and through wiring.
- ♦ Electronic class P, thermally protected ballasts standard.
- ♦ Green ground screw installed in channel.
- ♦ All fixtures come equipped with ballast disconnect to meet NEC code 410.73.

APPROVALS

- ♦ ETL Listed. Suitable for dry and damp locations with ETL Damp Label.



ORDERING GUIDE

Fill in the boxes below with the corresponding **bold** options.

Example: **LA603-4-3-32-T8-B8IN-MV-AC48**

LA603		3		T8	B8IN	MV	AC48				
SERIES	FIXTURE LENGTH	NO. OF LAMPS	WATTAGE	LAMP TYPE	BALLAST TYPE	VOLTAGE	MOUNTING	OPTIONS			
LA603	T8						AC48				
	4 4FT.	3	32	T8	B8IN	MV	Aircraft Cable 48" Length	EM1	Emergency Battery Back Up, 1 Lamp Operation		
	8 8FT.	3	32-TAN	T8	B8IN	MV		EM2	Emergency Battery Back Up, 2 Lamp Operation		
								2C	2 Circuit		
								DIM	Dimming—Consult Factory		

Consult Factory for additional configurations and options not listed or shown.

Note:

TAN—Tandem Units, double the number of lamps

Ballast

B8IN T8, Instant Start NBF (Standard)

Voltage

MV 120-277V

DIMENSIONS

