

OVERVIEW

- ♦ The LA616 is an innovative, architectural luminaire providing direct and indirect light distribution. With its transparent acrylic lens, the LA616 gives the perfect illusion to any modern application of light floating in mid-air.

FEATURES

- ♦ Available in 4ft. / 8ft. nominal lengths.
- ♦ 70% direct light distribution.
- ♦ 30% indirect light distribution.
- ♦ CRI greater than 80.
- ♦ Rated Life [L70] — 50,000 Hours.
- ♦ Fixture lumens per watt ratios [LpW] — Greater than 88.
- ♦ 120-277V (50/60Hz)
- ♦ 0-10V Dimming.

HOUSING

- ♦ Extrusion aluminum material with screw-less end caps.

LENS

- ♦ Polycarbonate lens provides a soft, evenly diffused light.

PROJECT _____

TYPE _____

QTY. _____

APPLICATIONS

- ♦ Lobbies
- ♦ Conference Rooms
- ♦ Showrooms
- ♦ Libraries
- ♦ Offices

INSTALLATIONS

- ♦ Designed for pendant mount with adjustable aircraft cable. Sliding brackets are provided for easy installation.
- ♦ Cable suspends 48" from ceiling. Other lengths available.
- ♦ Available as individual units or in continuous run applications supporting up to 550 watts.
- ♦ Suitable for wall mount applications with wall brackets.

LED

- ♦ Custom designed LED system with unique optics ensures perfectly even illumination.
- ♦ Dimming down to 10% on 0-10V dimming controls is standard.

WARRANTY

- ♦ 5 year limited warranty is standard.
- Exclusions may apply. Contact factory for terms and conditions.*

ORDERING GUIDE

Fill in the boxes below with the corresponding **bold** options.

Example: **LA616-4-51L-40K-U-D2**

LA616				U	D2			
SERIES	FIXTURE LENGTH	NOMINAL LUMENS	COLOR TEMP.	VOLTAGE	DIMMING	FINISH	OPTIONS	
LA616	4 4FT. 8 8FT.	4FT. 51L 5100 8FT. 66L 6600	30K 3000K 40K 4000K 50K 5000K	U 120-277V	D2 0-10V Dimming to 10%*	WH White BK Black GR Grey	Emergency E5 Emergency Battery Back-Up, 500 Lumens E7 Emergency Battery Back-Up, 700 Lumens E10 Emergency Battery Back-Up, 1000 Lumens E13 Emergency Battery Back-Up, 1300 Lumens Mounting WB Wall Brackets for Wall Mount	

*Compatible with 0-10V dimmers.

4FT. LUMEN PACKAGE					
Nominal Lumens	Color Temp.	Power (W)	Delivered Lumens	LpW	UL
5100	3000K	55W	4953	89	✓
	4000K	56W	5340	97	✓
	5000K	55W	5246	95	✓


8FT. LUMEN PACKAGE					
Nominal Lumens	Color Temp.	Power (W)	Delivered Lumens	LpW	UL
6600	3000K	75W	6300	84	✓
	4000K	75W	6594	88	✓
	5000K	75W	6975	93	✓

PHOTOMETRICS

Photometric reports are available at www.ullighting.net

DIMENSIONS

END VIEW



FIXTURE SIZE			
Nominal Size	Length (L)	Width (W)	Height (H)
4FT.	47.50 in.	276 in.	4.33 in.
8FT.	94.76 in.	276 in.	4.33 in.