



PROJECT _____

TYPE _____

QTY. _____

OVERVIEW

- ♦ LED T8 Tube

FEATURES

- ♦ Works with 99% of Instant Start Ballasts
- ♦ Bypass Ballast For Efficiency
- ♦ Plug 'N' Play for Quick Installation
- ♦ Internal Driver

APPLICATIONS

- ♦ Office spaces
- ♦ Hallways
- ♦ Stores and general lighting
- ♦ Basements
- ♦ Suggested ceilings max 10' feet

LISTINGS/QUALIFICATIONS

- ♦ UL LISTED
- ♦ DLC
- ♦ RoHS COMPLIANT



WARRANTY

- ♦ 5 year limited warranty is standard.
Exclusions may apply. Contact factory for terms and conditions.

ELECTRICAL	
INPUT VOLTAGE	120-277VAC
POWER FACTOR	>0.9
PHOTOMETRICS	
CRI	>80
BEAM ANGLE	120°

ORDERING GUIDE

Fill in the boxes below with the corresponding **bold** options.

Example: **LEDT8-4-12W-40K-U**

LEDT8	4			U
SERIES	TUBE LENGTH	WATTAGE	COLOR TEMP.	VOLTAGE
LEDT8	4 48"	12W 12 Watts 15W 15 Watts 18W 18 Watts	30K 3000K 40K 4000K 50K 5000K	U 120-277V

ITEM NO.	LENGTH	WATTAGE	LUMENS	LpW	COLOR TEMP.	VOLTAGE	CONNECTION
T8LED-4-12W-40K-D	4FT.	12W	1825	113	4000K	100-277V	DOUBLE
T8LED-4-15W-40K-D	4FT.	15W	2140	112	4000K	100-277V	DOUBLE
T8LED-4-18W-40K-D	4FT.	18W	2489	113	4000K	100-277V	DOUBLE