

LEDREADY



STEEL WHITE REFLECTOR

OVERVIEW

- ♦ General-purpose industrial style luminaire featuring a wide symmetrical reflector, which shields and controls the output of the lamps.
- ♦ Available with 2 lamps.

LED TUBES

- ♦ 120-277V (50/60Hz)
- ♦ Rated Life [L70] — 50,000 Hours.
- ♦ Wired for single or double end.
- ♦ Approximately 40% more energy efficient than standard F32T8 Lamps.

Assembled with no ballast

LISTINGS/QUALIFICATIONS

- ♦ Fixture Housing is ETL C/US Listed
- ♦ LED Tubes are ETL or UL C/US Listed and DLC Certified
- ♦ Proudly Made in America



PROJECT _____

TYPE _____

QTY. _____

APPLICATIONS

- ♦ Industrial
- ♦ Commercial
- ♦ General Lighting Areas

INSTALLATIONS

- ♦ Suitable for individual or continuous row mounting. May be surface mounted or suspended on stems, cables, or rods.

CONSTRUCTION

- ♦ Housing—Die formed from code gauge cold rolled steel. End plates quickly convert to snap-in continuous row joiners for uninterrupted wireway. Easy install socket plates have snap-in action. Reflectors attach with quarter-turn fasteners for easy installations and maintenance. Two reflectors with provided aligners are used on all 6Ft. and 8Ft. fixtures. Sufficient knockouts are provided on the back and ends for all electrical connection. Baked white enamel finish provides a minimum reflectivity of 87%. Optional 20GA housing is available
- ♦ Sockets—1/4 twist bi-pin or optional rotary locking type.
- ♦ Apertured Reflector—Allows approximately 10% uplighting, which reduces harsh contrasting with a completely dark ceiling. Fills the volume of space more evenly making it a more comfortable environment.

ORDERING GUIDE

Fill in the boxes below with the corresponding **bold** options.

Example: **LTIND200-2-T8-4-S**

LTIND200	2	T8							
SERIES	NO. OF TUBES	TYPE (LED TUBES)	TANDEM (TAN)	FIXTURE LENGTH	WIRED	OPTIONS			
LTIND200	2	T8	-	4 48" Length	S	Wire Guard			
	2	T8	TAN	8 96" Length	D	WGW	Wire Guard (24" / 36" / 48") *		
	2	T8	-	8 96" Length		Emergency			
						EM5	Emergency Battery Back Up, 500 Lumens - 1 Lamp		

TANDEM

Tandem Units, use double the number of tubes


CONSULT FACTORY FOR WATTAGE, LUMENS AND COLOR TEMPERATURE.

* WIRE GUARDS

For 96" fixtures, use 2 48" wire guards

DIMENSIONS

END VIEW



END VIEWS

