

LEDREADY



OVERVIEW

- ♦ Architectural linear luminaire with a compact six-inch square profile. Provides controlled direct down-light illumination.
- ♦ Continuous row mounting capability
- ♦ Clear, prismatic, acrylic diffuser
- ♦ Clean appearance. No exposed fasteners

LED TUBES

- ♦ 120-277V (50/60Hz)
- ♦ Rated Life [L70] — 50,000 Hours.
- ♦ Wired for single or double end.
- ♦ Approximately 40% more energy efficient than standard F32T8 Lamps.

Assembled with no ballast

LISTINGS/QUALIFICATIONS

- ♦ Fixture Housing is ETL C/US Listed
- ♦ LED Tubes are ETL or UL C/US Listed and DLC Certified
- ♦ Proudly Made in America



PROJECT _____

TYPE _____

QTY. _____

APPLICATIONS

- ♦ Commercial environments
- ♦ Retail Locations
- ♦ Offices
- ♦ Schools

INSTALLATIONS

- ♦ Pendant and surface mount.
- ♦ Designed for individual or continuous runs. Surface mount or suspended from ceilings on auxiliary hanging hardware. Sufficient knockouts are provided on the back of the housing for all electrical connections.

CONSTRUCTION

- ♦ Housing—Die formed code grade heavy gauge cold rolled steel with end caps welded into place for strength, uniformity and appearance. Half-end option allows for continuous run of the louver or diffuser as it passes from fixture-to-fixture. Plain-end option eliminates the knockout if not needed for electrical entry.
- ♦ Louvers and Diffusers—Call factory. Parabolic cross blades in semi-specular or white aluminum are standard shielding media. Acrylic prismatic pattern #12 is standard diffusing media.
- ♦ Finish—All steel housing parts are painted after fabrication with a white powder coating. Provides a reflectivity of 90% or greater. Optional colors on request.

ORDERING GUIDE

Fill in the boxes below with the corresponding **bold** options.

Example: **LTLA610-2-T8- - - - AC48 - - -**

LTLA610	2	T8			AC48			
SERIES	NO. OF TUBES	TYPE (LED TUBES)	TANDEM (TAN)	FIXTURE LENGTH	MOUNTING	WIRED	OPTIONS	
LTLA610	2	T8	-	4 48" Length	AC48 Aircraft Cable	S	Wired for Singled End	<div>Emergency</div> <div>EM5</div> <div>Emergency Battery Back Up, 500 Lumens - 1 Lamp</div> <div>To operate, must use an electronic instant start ballast</div> <div>EM14</div> <div>Emergency Battery Back Up, 1400 Lumens - 1 Lamp</div> <div>To operate, must use an electronic instant start ballast</div>
	2	T8	TAN	8 96" Length		D	Wired for Double End	
<div>TANDEM</div> <div>Tandem Units, use double the number of tubes</div>								
<div>Dimming Systems</div> <div>DLT4</div> <div>Dimmable Systems Including driver and LED tubes (1 or 2 LED Tubes)</div> <div>48" Length (Keystone)</div>								


TANDEM

Tandem Units, use double the number of tubes

CONSULT FACTORY FOR WATTAGE, LUMENS AND COLOR TEMPERATURE.

DIMENSIONS

END VIEW



BACK VIEW

