

LEDREADY



PROJECT _____

TYPE _____

QTY. _____



OVERVIEW

- ♦ The LTSC102 is a shallow open strip linear luminaire.
- ♦ Ideal for conventional fluorescent replacement applications.
- ♦ Available in 2ft., 3ft., and 4ft. nominal lengths.

LED TUBES

- ♦ 120-277V (50/60Hz)
- ♦ Rated Life [L70] — 50,000 Hours.
- ♦ Wired for single or double end.
- ♦ Approximately 40% more energy efficient than standard F32T8 Lamps.

Assembled with no ballast

LISTINGS/QUALIFICATIONS

- ♦ Fixture Housing is ETL C/US Listed
- ♦ LED Tubes are ETL or UL C/US Listed and DLC Certified
- ♦ Proudly Made in America



APPLICATIONS

- ♦ Coves
- ♦ Industrial Racks
- ♦ Workshops
- ♦ Retail Shelving
- ♦ Utility Areas
- ♦ Warehouses

INSTALLATION

- ♦ Suitable for individual or continuous row mounting. May be surface mounted or suspended on stems, cables, or rods.

CONSTRUCTION

- ♦ Housing—Die formed from code gauge cold rolled steel. End plates quickly convert to snap-in continuous row joiners for uninterrupted wireway. Easy install socket plates have snap-in action. Wireway covers snap on or off for easy installation and maintenance. Optional screw-down covers for tight coves or added security. Sufficient knockouts are provided on the back and ends for all electrical connections. Baked white enamel finish provides a minimum reflectivity of 87%. Optional 20GA housing is available.
- ♦ Push-up sockets

ORDERING GUIDE

Fill in the boxes below with the corresponding **bold** options.

Example: **LTSC102-1-T8-4-S**

SERIES	NO. OF TUBES	TYPE (LED TUBES)	FIXTURE LENGTH	WIRED	OPTIONS
LTSC102	1	T8	2 24" Length	S Wired for Singled End	Dimming Systems
	1	T8	3 36" Length	D Wired for Double End	DLT2 Dimmable Systems Including driver and LED tubes (1 LED Tube) 24" Length (Keystone)
	1	T8	4 48" Length		DLT4 Dimmable Systems Including driver and LED tubes (1 LED Tube) 48" Length (Keystone)

CONSULT FACTORY FOR WATTAGE, LUMENS AND COLOR TEMPERATURE.

DIMENSIONS

