



### FEATURES

- ◆ Available with 4" trim
- ◆ Compatible with most 4" recessed housings
- ◆ E26 Medium base socket adapter included
- ◆ CRI greater than 95
- ◆ Rated Life [L70] — 50,000 Hours
- ◆ Fixture lumens per watt ratios [LpW] — Greater than 57
- ◆ Dimmable at 120V
- ◆ Mercury Free
- ◆ 5 year limited warranty is standard

### LISTINGS/QUALIFICATIONS

- ◆ UL C/US
- ◆ Suitable for Wet Locations
- ◆ Energy Star



### Dimmer Compatibility


Brand	Model	Brand	Model
LEVITON	DSL06	LUTRON	CTCL-153P
LEVITON	IPL06	LUTRON	DVCL-153P
LEVITON	6674		

### ORDERING GUIDE

Fill in the boxes below with the corresponding **bold** options.

Example: **RB-4S-7L-30K-1-D3**

<b>RB</b>	<b>4S</b>	<b>7L</b>		<b>1</b>	<b>D3</b>
SERIES	FIXTURE SIZE	NOMINAL LUMENS	COLOR TEMP.	VOLTAGE	DIMMING
<b>RB</b>	<b>4S</b> 4" Square	<b>4N.</b>	<b>30K</b> 3000K <b>40K</b> 4000K	<b>1</b> 120V	<b>D3</b> Dimmable 120V
		<b>7L</b> 750			



### Lumen Packages

Item No.	Order Code	Size	Nominal Lumens	Delivered Lumens	Color Temp.	Watts	LpW	Dimmable	UL	Energy Star
RB4S730	RB-4S-7L-30K-1-D3	4"	750	715	3000K	10W	72	120V	✓	✓
RB4S740	RB-4S-7L-40K-1-D3	4"	750	760	4000K	10W	76	120V	✓	✓

- This unit is designed to be compatible with most leading edge or incandescent style rotary or slide type dimmers.(Dimming range 100% - 5%) Fixture performance may vary depending on dimmer manufacturer and circuit loading.  
- Avoid mixing load types on the same circuit: Do not dim LED while also dimming CFL or incandescent loads.